



ISO 9001:2008 ED ISO 14001:2004
CERTIFICATO Nr. 501005957 Rev. 02
CERTIFICATO Nr. 501008826

VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.
www.valpaint.it E-mail: info@valpaint.it

SC 00229

Q60

Technical Sheet:

NAME:	Q60
TYPE:	water based paint
USE:	to add to any shades of Polistof to get the Shantung Fabric effect.
TECHNICAL DATA:	specific weight: 1.000 ± 30 gr/LT. at 20°C viscosity: = = = yield: LT. 0,200 per LT. 1 of POLISTOF LT. 1 per LT. 5 of POLISTOF colours: Col. 500 packaging: LT. 0,200 - LT. 1 on the surface: = = = overpainting: = = = below the painting: = = =
DRYING TIME:	
CHARACTERISTICS AND RESISTANCE:	product stable to light and resistant to washing. Available in Colour 500 to add to any Polistof shades = = =
PREPARATION OF THE SURFACE:	
PREPARATION OF THE PRODUCT:	dilution: ready to use. Add to Polistof and mix adequately. It is possible to add also L 50 col. 301 to Polistof. catalization relation : = = = pot life: = = = system: pour the product Q60 in Polistof pack and mix well coats: = = = stability: 2 years approximately in pack well closet and never opened
APPLICATION:	

NOTES:

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with water and soap. Keep away from freezing

Technical Sheet n° SC 00229 issued by the Control Quality Department:

Edition n° 1

February 2011