



VALPAINT S.p.A. Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY Tel. +39 071 906383 (r.a.) - Fax +39 071 906384 E-mail: info@valpaint.it C.F./P.IVA/R.I. di AN 01108220425 Capitale Sociale € 500.000,00 i.v.

www.valpaint.it -

SC 00037

## CERA LUCIDANTE 370

NAME:	CERA LUCIDANTE 370	
TYPE:	water-repellent waxes	
<u>USE:</u>		or walls finished with Stucco Antico, Marmorino,
	Grassello di Calce, Arteco', wallpaper, furniture, floors.	
TECHNICAL DATA:	specific weight:	790±20gr./LT. at 25 °C
	viscosity:	===
	yield:	10-20 $m^2/lt$ depending on the absorption of the surface, on the consistence of the polished and on the resistance that want to obtain
	aspect:	pasty
	colours:	transparent after drying
	packaging:	cans of 1 lt 4 lt.
DRYING TIME:	on the surface:	2 hours at 20°C
	over painting:	===
	below the surface:	8 hours at 20°C
CHARACTERISTICS AND	high level of waterproof	ing and washability of the treat walls
<b>RESISTANCE:</b>		
PREPARATION OF THE		
SURFACE:		
<b>PREPARATION OF THE</b>	thinning:	ready for use
PRODUCT:	0	5
	catalization relation:	===
	pot life:	===
APPLICATION:	system:	steel spatula, - trowel - brush. After drying,
		glossy the surface with woollen cloth
	coats:	1 or more depending on desired effect

## NOTE:

Cera Lucidante 370 is made of beeswax mixed with white spirit. Keep out of range of the children.

Technical Sheet n° SC 00037 issued by the Control Quality Dpt.: Edition n° 3 October 2006