



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00179

SETOMAT

Technical Sheet

NAME:

SETOMAT

TYPE:

water-based additive

USE

additive to add to VALSETIN

CHARACTERISTICS:

specific weight: 2.000 ± 30 gr/LT. at 20°C

viscosity: = = =

yield: LT. 0,100 per LT. 1 of VALSETIN

LT. 0,400 per LT. 4 of VALSETIN

aesthetic effect: = = =

colours: = = =

packaging: LT. 0,100 - LT. 0,400

DRYING:

on the surface: = = =

over painting: = = =

in depth: = = =

CHARACTERISTICS AND RESISTANCE:

water-based additive to add to VALSETIN to get the particular Wallpaper Silk Effect and the Flowered Silk Effect as stated in VALSETIN catalogue.

PRODUCT PREPARATION:

= = =

dilution: ready to use; add to VALSETIN mixing carefully.

catalisation relation: = = =

pot life: = = =

APPLICATION:

system : Add a package of LT. 0,400 of SETOMAT, to LT. 4 of VALSETIN already coloured, or pour LT. 0,100 of SETOMAT in one package of LT. 1 of VALSETIN.

number of coatings: = = =

NOTE: The temperature of application and of stocking must not be inferior to +5°C and superior to +30°C. It is suggested to keep away from the sun and from the frost. Tools must be cleaned soon after use with water and soap.

Technical Sheet n° SC 00179 issued by the Control Quality Department

Edition n° 2

April 2005