



ISO 9001:2008 ED ISO 14001:2004
CERTIFICATO Nr. 501005957 Rev. 02
CERTIFICATO Nr. 501008826

VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.
www.valpaint.it E-mail: info@valpaint.it

SC 00232

V30

Technical sheet:

NAME:

V30

TYPE:

water-base paint

USE:

add to any colour of Valsetin to get the SOFT Effect.

TECHNICAL DATA

specific weight: 1.655 ± 30 gr/LT. at 20°C

viscosity: = = =

yield: 0,250 l in 1l of VALSETIN

1 l per 4 l of VALSETIN

packaging: 0,250 l – 1 l

DRYING TIME:

on the surface: = = =

overpainting: = = =

below the painting: = = =

CHARACTERISTICS AND RESISTANCE

Product stable to light to be added in any colours of Valsetin. Resistant to washings only after applying one or more coatings (depending on the washing resistance demanded) of Finish V 16 by roller.

= = =

PREPARATION OF THE SURFACE :

PREPARATION OF THE NE PRODUCT:

dilution: ready to use. Add to Valsetin and mix well..

catalization relation: = = =

pot life: = = =

APPLICATION:

system: pour V 30 in Valsetin and mix well

number of coating: = = =

stability: 2 years approximately in well sealed and never opened pack..

NOTES:

The temperature of application must be not inferior to +5°C and not superior to +30°C. Tools must be cleaned soon after use with water and soap.

Technical Sheet n° SC 00232 issued by the Control Quality Department:

Edition n° 1

August 2011