



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it • www.valpaintjungle.it

SC 00224

L50

Technical Sheet:

NAME:

L50

TYPE:

water based paint

USE:

to add in Artecò 7 already coloured to obtain the metallic finished both in the Classic and Floral effects. It can be add also to any Polistof shades to have Velvet Fabric Effect with L50 or Shantung Fabric Effect always with L50.

TECHNICAL DATA

specific weight:

1.020 - 1.200 ± 30 gr/LT. at 20°C

viscosity:

===

yield:

2 X LT. 0,100 per LT. 1 of ARTECO' 7
LT. 0,500 per LT. 2,5 of ARTECO' 7
2 X LT. 0,500 per LT. 5 of ARTECO' 7
LT. 0,100 per LT. 1 of POLISTOF
LT. 0,500 per LT. 5 of POLISTOF

colours:

colours from the catalogue

packaging:

LT.0,100 - LT. 0,500

DRYING TIME :

on the surface:

===

overpainting:

===

below the painting :

===

CHARACTERISTICS AND

RESISTANCE:

product stable to light and resistant to washing. Available in 6 different shades to add in Artecò 7 already coloured or in any Polistof Shades

PREPARATION OF THE

===

SURFACE:

PREPARATION OF THE

dilution:

ready to use. Add to Artecò 7 and mix adequately

PRODUCT :

Catalization relation:

===

pot life:

===

APPLICATION:

system:

pour the product L50 in Artecò 7 pack or Polistof and mix well.

coats:

===

stability:

2 years approximately in pack well closed and never opened.

NOTES:

Application temperature must be between +5°C and +30°C. Wash the tools soon after use with water and soap. Keep away from freezing.

Technical Sheet n° SC 00224 issued by the Control Quality Department:

Edition n° 3

July 2012