



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00036

FINISH V 12

Technical Sheet

NAME:

FINISH V 12

TYPE:

transparent paint

USE:

silicone-based transparent protection for interior formulated and tested to protect Arteco'.

TECHNICAL DATA:

specific weight: 1.010 gr/LT. at 25°C

viscosity: = = =

yield: 20 - 25 m²/LT.

aspect: satined

colours: transparent

packaging: can of 1LT.

on the surface: 1 hour at 20°C

overpainting: 8 hours at 20°C

below the surface: 12 hours at 20°C

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

if it is applied on Arteco' it avoids colour fading and lime efflorescent in Arteco'. Wall transpiration is on the basis of DIN rule 52615 (detaching and support-sticking resistance DIN ISO 4624)

PREPARATION OF THE SURFACE:

PREPARATION OF THE PRODUCT:

thinning: Finish V 12 = 1 part
Drinkable water = 1 part

catalization relation: = = =

pot life: = = =

APPLICATION:

system: use a brush in a circular way as Arteco' application

coats: 1 (the paint tends to become shiny with 2 coats)

NOTE:

Do not apply the product if the temperature is below to +5°C

Technical Sheet n° SC 00036 issued by the Control Quality Department

Edition n°4 May 2004